

PT SEIV Indonesia

Paint Industry - Tangerang



TECHNICAL DATA SHEET

SEIV DUAN ALPRIME

Product code: 467.xxx.xx

I. PRODUCT DESCRIPTION

SEIV ALPRIME is an alkyd primer which use special pigment that gives corrosion resistant, good adhesion, and fast dry. It can be used as primer of alkyd paint.

II. RECOMMENDED USE

Can be use as primer of alkyd paint. Suitable for new substrate or repainting.

III. SUBSTRATE

Applied on metal and wood

IV. TECHINCAL INFORMATION

Color : According colors card and special order

Finish : High build matt/doff

Density : 1.30 - 1.50 g/ml

Solid content : approximately 65% by weight

Gloss level (GU 60°) : < 10

Thickness per layer (by spray) : DFT 25 - 35 µm

Theoretical coverage $: 13 - 19 \text{ m}^2/\text{Liter/coat}$

Drying time, Touch dry : 30 - 60 minutes at 30 °C

Hard dry : 4 - 8 hours at 30 °C

Coating Interval : 4 hours

V. <u>APLICATION DATA</u>

Remarks : Handle with care. Stir well before used

Application method : by brush, roller or spray-gun

Thinner : SEIV Thinner B

Dilution : 0 - 10% for application with brush or roller

15 – 30% for application with spray-gun



PT SEIV Indonesia

Paint Industry - Tangerang



2

TECHNICAL DATA SHEET

SEIV DUAN ALPRIME

VI. FEATURES & BENEFITS

- 1. Corrosion resistant
- 2. Fast dry

VII. SURFACE PREPARATION & APPLICATION

A. SURFACE PREPARATION

The substrate must be sound, clean, dry and free form dust, dirt, waxes, oil etc. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed.

B. APPLICATION

Recommended paint system:

1. Primer

SEIV Duan ALPRIME: 2 coats. Total number of coats depended on requirement.

2. Topcoat

All type of synthetic paint

VIII. STORAGE & PACKING

Storage: The product must be stored in accordance with nation regulations. Preferred

storage condition is cool / room temperature & dry space provided with adequate

ventilation. The containers should be sealed tightly.

Packing : 5 kg, and 20 kg

IX. HEALTH & SAFETY

Please read the precaution notices displayed on the can. Spray under well-ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Head Office: HARKOT TRADE CENTER, Lantai 2 No. 58 - Jl. Merdeka No. 53, Tangerang 15111, Indonesia

Telp. 62-21 55791111 (hunting) | Fax: 62-21 55760533 / 34 | www.seiv.co.id



PT SEIV Indonesia

Paint Industry - Tangerang



TECHNICAL DATA SHEET

SEIV DUAN ALPRIME

X. DISCLAIMER

The information in this data sheet is given on the best on laboratory testing and practical experience. However as the product is often used under condition beyond our control, we can not guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.