



## TECHNICAL DATA SHEET

### SEIV ELASKO

**Product code : 432.xxx.xx**

#### **I. PRODUCT DESCRIPTION**

*SEIV Elasko* is a waterproofing coating which can close hairline cracks on the wall & rooftop. Can be applied on concrete, chamfer/gutter and exterior wall. It has good adhesion, good weather stability, anti fungi, anti algae and easy to apply.

#### **II. RECOMMENDED USE**

For exterior application.

#### **III. SUBSTRATE**

Applied on concrete, rooftop & plastering.

#### **IV. TECHINCAL INFORMATION**

Color	: White and according to color card
Finish	: Semi gloss
Density	: 1.10 – 1.30 g/ml
Solid content	: approximately 53% by weight
Gloss level (GU 60°)	: NA
Thickness per coat	: DFT 25 – 30 µm
Theoretical coverage	: 1 – 2 m <sup>2</sup> / kg
Drying time, Touch dry	: 20 - 30 minutes at 30 °C
Hard dry	: ± 2 hours at 30 °C
Coating Interval	: 2 hours

#### **V. APLICATION DATA**

Remarks	: Handle with care. Stir well before used
Application method	: by brush, roller
Thinner	: <b>Water</b>
Dilution	: ca. 5% for application with brush



## TECHNICAL DATA SHEET

### SEIV ELASKO

ca. 10% for application with roller

#### VI. FEATURES & BENEFITS

1. Elastic
2. Durable coating
3. Good waterproofing
4. Good weathering resistant
5. Anti-fungal & anti algae

#### VII. SURFACE PREPARATION & APPLICATION

##### A. SURFACE PREPARATION

The substrate must be sound, clean, dry and free from dust, dirt, waxes, oil etc. All existing coatings must be thoroughly removed by **SHRED Paint Remover** to ensure adequate adhesion. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/ loose particles must be removed.

##### B. APPLICATION

Recommended paint system:

1. **Primer** : NA
2. **Topcoat**

*SEIV Elasko*: 2 coats

#### VIII. STORAGE & PACKING

**Storage** : The product must be stored in accordance with nation regulations. Preferred storage condition is cool / room temperature & dry space provided with adequate ventilation. The containers should be sealed tightly.

**Packing** : 1 kg, 4 kg and 20 kg

#### IX. HEALTH & SAFETY

Please read the precaution notices displayed on the can. Apply under well-ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should



## **TECHNICAL DATA SHEET**

### **SEIV ELASKO**

immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

#### **X. DISCLAIMER**

The information in this data sheet is given on the best on laboratory testing and practical experience. However as the product is often used under condition beyond our control, we can not guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.