



TECHNICAL DATA SHEET

SEIV FLAT WALL PAINT

Product code : 420.xxx.xx

I. PRODUCT DESCRIPTION

SEIV Flat Wall Paint is an economist interior emulsion paint which made from acrylic copolymer resin with selected pigments and fillers. It is economical, easy to apply, fast dry, good adhesion and middle hiding power.

II. RECOMMENDED USE

For interior application. Suitable for new substrate or repainting

III. SUBSTRATE

Applied on wall, gypsum, concrete, asbestos and ceiling

IV. TECHNICAL INFORMATION

Color	: White and according to color card
Finish	: Doff/ Matt
Density	: 1.58 – 1.68 g/ml
pH	: 8.5 – 9.0
Solid content	: 60 – 65% by weight
Thickness	: DFT 25 - 35 μ m
Theoretical coverage	: 5 – 7 m ² /Liter/ coat
Drying time, Touch dry	: ca. 30 minutes at 30 °C
Hard dry	: ca. 2 hours at 30 °C
Coating Interval	: Min. 2 hours

V. APPLICATION DATA

Remarks	: Handle with care. Stir well before used
Application method	: by brush, roller
Thinner	: Water



TECHNICAL DATA SHEET

SEIV FLAT WALL PAINT

Dilution : diluted by water 5 – 10%

VI. FEATURES & BENEFITS

1. No splatter
2. Environmental friendly
3. Fast dry
4. Good hiding power
5. Anti-fungi
6. Free mercury and lead
7. Wash-able

VII. SURFACE PREPARATION & APPLICATION

A. SURFACE PREPARATION

The substrate must be sound, clean, dry and free from dust, dirt, waxes, oil etc. All existing coatings must be thoroughly removed by SHRED Paint Remover to ensure adequate adhesion. Any resulting dust/ loose particles must be removed.

B. APPLICATION

Recommended paint system :

1. Primer

SEIV Magnoprime-Alkali Resistant Primer or SEIV Magnoprime Interior : 1 coat (highly recommended for new substrate or repainting).

2. Topcoat

SEIV Flat Wall Paint : 2 -3 coats or apply the paint as a need. Total number of coats depended on hiding power of colored paint. After coating, if there is paint in the can, close the can tightly and clean the tools thoroughly.

VIII. STORAGE & PACKING

Storage : The product must be stored in accordance with nation regulations. Preferred storage condition is cool / room temperature & dry space provided with adequate ventilation. The containers should be sealed tightly.



TECHNICAL DATA SHEET

SEIV FLAT WALL PAINT

Packing : 5 kg, 25 kg.

IX. HEALTH & SAFETY

Please read the precaution notices displayed on the can. Apply under well-ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

X. DISCLAIMER

The information in this data sheet is given on the best on laboratory testing and practical experience. However as the product is often used under condition beyond our control, we can not guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.