



TECHNICAL DATA SHEET

SEIV FLINTKOTE

Kode produk : 445.007.00

I. PRODUCT DESCRIPTION

SEIV Flintkote Undercover Agent is a bituminous based paint. It gives good corrosion resistant, good adhesion, waterproof, fast dry, and heat resistant (until 120 °C).

II. RECOMMENDED USE

Can be used for automotive and protective application. Suitable for new substrate or repainting.

III. SUBSTRATE

Applied on metal, concrete, machine, rooftop and gutter

IV. TECHNICAL INFORMATION

Color	: Black
Finish	: Textured and Semi-Gloss
Density	: 1.02 – 1.12 g/ml
Solid content	: approximately 55% by weight
Thickness per coat	: DFT 25 - 30 µm
Theoretical coverage	: 6 – 7 m ² / Liter
Drying time, Touch dry	: 30 - 40 minutes at 30 °C
Hard dry	: about 2 hours at 30 °C
Coating Interval	: 2 hours

V. APPLICATION DATA

Remarks	: Handle with care. Stir well before used
Application method	: by brush
Thinner	: SEIV Thinner B
Dilution	: 20 – 30% for application by brush



TECHNICAL DATA SHEET

SEIV FLINTKOTE

VI. FEATURES & BENEFITS

1. Rush guard
2. Cover leak or imperfection substrate
3. Water proofing
4. Durable coating

VII. SURFACE PREPARATION & APPLICATION

A. SURFACE PREPARATION

The substrate must be sound, clean, dry and free from dust, dirt, waxes, oil etc. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed.

B. APPLICATION

Recommended paint system :

1. **Primer** : NA
2. **Topcoat**

SEIV Flintkote : 3 coats or can be applied as needed. Total number of coats depended from porosity of substrate or imperfection of the substrate and purpose of painting.

Note

1. For waterproofing : apply 3 layers. For the best result, add concrete on the top of coating.
2. For crack on concrete : Use pallet knife for application and don't dilute the paint. Give interval over-coating hours per layer
3. For sound damping (car under body coating) : apply 3 layers

VIII. STORAGE & PACKING

Storage : The product must be stored in accordance with nation regulations. Preferred storage condition is cool / room temperature & dry space provided with adequate ventilation. The containers should be sealed tightly.

Packing : 1 kg, 5 kg and 20 kg



TECHNICAL DATA SHEET

SEIV FLINTKOTE

IX. HEALTH & SAFETY

Please read the precaution notices displayed on the can. Spray under well-ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

X. DISCLAIMER

The information in this data sheet is given on the best on laboratory testing and practical experience. However as the product is often used under condition beyond our control, we can not guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.