



TECHNICAL DATA SHEET

SEIV GLINTONE

Product code : 448.xxx.xx

I. PRODUCT DESCRIPTION

SEIV Glintone (Exterior Solvent Base) is wood & metal coating for exterior & interior application based on acrylic resin. Excellent adhesion, rust protection & weather resistance for 5 years. Chrome Lead Free and No Added Mercury.

II. RECOMMENDED USE

For exterior & interior application, suitable for new substrate or repainting.

III. SUBSTRATE

Applied on metal and wood

IV. TECHNICAL INFORMATION

Color	: According color cards and special order
Finish	: Smooth & glossy
Density	: 0.85 – 1.00 g/ml
Solid content	: approximately 40 - 50% by weight
Gloss level (GU 60°)	: > 85
Thickness per coat (by brush)	: DFT 20 – 25 µm
Theoretical coverage	: 10 – 12 m ² / Liter/ coat
Drying time, Touch dry	: ± 15 minutes at 30 °C
Hard dry	: ± 1 hour at 30 °C
Coating Interval	: 1 hour

V. APPLICATION DATA

Remarks	: Handle with care. Stir well before used
Application method	: by brush, roller and spray-gun
Thinner	: Thinner B
Dilution	: max. 10% for application with brush



TECHNICAL DATA SHEET

SEIV GLINTONE

15 – 30% for application with spray-gun

VI. FEATURES & BENEFITS

1. 5 years weather resistant (color & gloss)
2. Anti peel-off / Good adhesion
3. Easy to apply
4. Fast dry
5. Rust protection
6. Environmental friendly

VII. SURFACE PREPARATION & APPLICATION

A. SURFACE PREPARATION

The substrate must be sound, clean, dry and free from dust, dirt, waxes, oil etc. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed. For recoating application is recommended to removed all old film, cleaned by *SHRED Paint Remover* to provide good adhesion power.

B. APPLICATION

Recommended paint system :

1. Primer

SEIV Chemolux Synthetic Primer: 1 coat

2. Topcoat

SEIV Glintone: 2 – 3 coats. Total number of coats depended on hiding power of colored paint.

VIII. STORAGE & PACKING

Storage : The product must be stored in accordance with nation regulations. Preferred storage condition is cool / room temperature & dry space provided with adequate ventilation. The containers should be sealed tightly.

Packing : 0.95 L, 5 L, and 20 L



TECHNICAL DATA SHEET

SEIV GLINTONE

IX. HEALTH & SAFETY

Please read the precaution notices displayed on the can. Spray under well-ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

X. DISCLAIMER

The information in this data sheet is given on the best on laboratory testing and practical experience. However as the product is often used under condition beyond our control, we can not guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.