

PT SEIV Indonesia

Paint Industry - Tangerang



TECHNICAL DATA SHEET

SEIV MAGNOCLEAN

Product code : 424.xxx.xx

I. **PRODUCT DESCRIPTION**

SEIV Magnoclean is premium wall paint for interior application with special formulation using nano-silver technology so can protect the wall from stains and bacteria.

II. **RECOMMENDED USE**

For interior application, suitable for new substrate or repainting.

III. **SUBSTRATE**

Applied on asbestos, wall, plastering, concrete and ceiling.

IV. **TECHINCAL INFORMATION**

Color		: White and according to colors card
Finish		: matt/ doff
Density		: 1.25 – 1.35 g/ml
рН		: 8.5 – 9.0
Solid content		: approximately 55% by weight
Thickness per coat		: DFT 25 – 35 μm
Theoretical coverage per coat		: $12 - 17 \text{ m}^2$ / Liter
Drying time,	Touch dry	: \pm 30 minutes at 30 °C
	Hard dry	: \pm 2 hours at 30 °C
Coating Interval		: 2 hours

V. **APLICATION DATA**

Remarks	: Handle with care. Stir well before used
Application method	: by brush, roller, spray air-less
Thinner	: Water
Dilution	: Diluted by water 5 – 10%

Head Office : HARKOT TRADE CENTER, Lantai 2 No. 58 - Jl. Merdeka No. 53, Tangerang 15111, Indonesia Telp. 62-21 55791111 (hunting) | Fax: 62-21 55760533 / 34 | www.seiv.co.id



PT SEIV Indonesia

Paint Industry - Tangerang



TECHNICAL DATA SHEET

SEIV MAGNOCLEAN

VI. <u>FEATURES & BENEFITS</u>

- 1. Easy clean any stains (Oil, crayon, marker, lipstick etc.)
- 2. No spatter
- 3. 5 years weather resistant (color)
- 4. Environmental friendly
- 5. Chrome Lead free & no Mercury
- 6. Soft appearance
- 7. Anti-algae & anti-fungi until 5 years
- 8. Excellent hiding power
- 9. Protecting the wall form any stains and bacteria

VII. SURFACE PREPARATION & APPLICATION

A. SURFACE PREPARATION

The substrate must be sound, clean, dry and free form dust, dirt, waxes, oil etc. All existing coatings must be thoroughly removed by **SHRED Paint Remover** to ensure adequate adhesion. Any resulting dust/loose particles must be removed.

B. APPLICATION

Recommended paint system:

1. Primer

SEIV Magnoprime-Alkali Resistant Primer: 1 coat (highly recommended for new substrate or repainting).

2. Topcoat

SEIV Magnoclean : 2 -3 coats or apply the paint as needed. Total number of coats depended on hiding power of colored paint. After coating, if there is paint in the container, close the container tightly and clean the tools thoroughly.

VIII. STORAGE & PACKING

Storage : The product must be stored in accordance with nation regulations. Preferred storage condition is cool / room temperature & dry space provided with adequate ventilation. The containers should be sealed tightly.

Packing : 2.5 L, 20 L

Head Office : HARKOT TRADE CENTER, Lantai 2 No. 58 - Jl. Merdeka No. 53, Tangerang 15111, Indonesia Telp. 62-21 55791111 (hunting) | Fax: 62-21 55760533 / 34 | www.seiv.co.id



PT SEIV Indonesia

Paint Industry - Tangerang



TECHNICAL DATA SHEET

SEIV MAGNOCLEAN

IX. <u>HEALTH & SAFETY</u>

Please read the precaution notices displayed on the can. Apply under well-ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

X. **DISCLAIMER**

The information in this data sheet is given on the best on laboratory testing and practical experience. However as the product is often used under condition beyond our control, we can not guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.