



## TECHNICAL DATA SHEET

### SEIV MAGNOLITE SUPERIOR QUALITY

**Product code : 422.xxx.xx**

#### **I. PRODUCT DESCRIPTION**

*SEIV Magnolite Superior Quality* is superior quality of interior emulsion paint based on pure acrylic resin designed to give smooth and egg shell appearance. It provides excellent hiding power, easy clean, fast dry, fungi and algae resistance, environmental friendly: odorless, free mercury and lead

#### **II. RECOMMENDED USE**

As topcoat for interior application. Suitable for new substrate or repainting.

#### **III. SUBSTRATE**

Applied on wall, gypsum, concrete, asbestos and ceiling

#### **IV. TECHNICAL INFORMATION**

Color	: White and according to color card
Finish	: Egg Shell
Density	: 1.38 – 1.55 g/ml
pH	: 8.5 – 9.0
Solid content	: 50 – 55% by weight
Thickness per coat	: DFT 25 - 35 $\mu$ m
Theoretical coverage	: 6 – 10 m <sup>2</sup> / L/ coat
Drying time, Touch dry	: ca. 30 minutes at 30 °C
Hard dry	: ca. 2 hours at 30 °C
Coating Interval	: Min. 2 hours

#### **V. APPLICATION DATA**

Remarks	: Handle with care. Stir well before used
Application method	: by brush, roller, spray air-less
Thinner	: <b>Water</b>
Dilution	: diluted by water 5 – 10%



## TECHNICAL DATA SHEET

### SEIV MAGNOLITE SUPERIOR QUALITY

#### VI. FEATURES & BENEFITS

1. Smooth and egg shell appearance
2. No splatter
3. Environmental friendly
4. Fast dry
5. Excellent hiding power
6. Anti-fungi
7. Free mercury and lead
8. Wash-able

#### VII. SURFACE PREPARATION & APPLICATION

##### A. SURFACE PREPARATION

The substrate must be sound, clean, dry and free from dust, dirt, waxes, oil etc. All existing coatings must be thoroughly removed by **SHRED Paint Remover** to ensure adequate adhesion.

##### B. APPLICATION

Recommended paint system :

###### 1. **Primer**

**SEIV Magnoprime - Alkali Resistant Primer** : 1 coat (highly recommended for new substrate or repainting).

###### 2. **Topcoat**

**SEIV Magnolite Superior Quality** : 2 coats or apply the paint as a need. Total number of coats depended on hiding power of colored paint. After coating, if there is paint in the can, close the can tightly and clean the tools thoroughly

#### VIII. STORAGE & PACKING

**Storage** : The product must be stored in accordance with nation regulations. Preferred storage condition is cool / room temperature & dry space provided with adequate ventilation. The containers should be sealed tightly.

**Packing** : 2.5 liters, 20 liters



## **TECHNICAL DATA SHEET**

### **SEIV MAGNOLITE SUPERIOR QUALITY**

#### **IX. HEALTH & SAFETY**

Please read the precaution notices displayed on the can. Spray under well-ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

#### **X. DISCLAIMER**

The information in this data sheet is given on the best on laboratory testing and practical experience. However as the product is often used under condition beyond our control, we can not guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.