

PT SEIV Indonesia

Paint Industry - Tangerang



TECHNICAL DATA SHEET

SEIV MAGNOPRIME INTERIOR

Product code: 425.100.10

I. PRODUCT DESCRIPTION

SEIV Magnoprime Interior is a high quality interior primer based on acrylic copolymer emulsion. It's very effective product to protect interior wall paint from efflorescent which caused by high alkalinity, and provide to improve hiding power of top coat along increase the adhesion power.

II. RECOMMENDED USE

Primer for all Emulsion Paint especially Interior wall paint (SEIV Magnolite, SEIV Magnosilk, SEIV Magnoclean, etc.). Suitable for new substrate or repainting.

III. SUBSTRATE

Applied on wall, gypsum, concrete and asbestos

IV. TECHINCAL INFORMATION

Color : White

Finish : Doff/ Matt

Density : 1.10 - 1.20 g/ml

Solid content : 35 - 40% by weight

Thickness per coat : DFT 18 - 22 µm

Theoretical coverage $: 10 - 12 \text{ m}^2/\text{Liter/coat}$

Drying time, Touch dry : ca. 30 minutes at 30 °C

Hard dry : 2 - 3 hours at 30 °C

Coating Interval : 2 hours

V. APLICATION DATA

Remarks : Handle with care. Stir well before used

Application method : by brush, roller, spray air-less

Thinner : NA

Dilution : NA



PT SEIV Indonesia

Paint Industry - Tangerang



TECHNICAL DATA SHEET

SEIV MAGNOPRIME INTERIOR

VI. <u>FEATURES & BENEFITS</u>

- 1. Ready to used
- 2. Environmental friendly
- 3. Easy to apply
- 4. Anti-fungi
- 5. Free mercury and lead
- 6. Provide hiding power
- 7. Increase adhesion power of interior wall paint

VII. SURFACE PREPARATION & APPLICATION

A. SURFACE PREPARATION

The substrate must be sound, clean, dry and free form dust, dirt, waxes, oil etc. All existing coatings must be thoroughly removed by *SHRED Paint Remover* to ensure adequate adhesion.

B. APPLICATION

Recommended paint system:

1. Primer

SEIV Magnoprime Interior: 1 coat

Make sure mix the wet paint well before used. After application, if there is present paint in the container, closed container tightly and clean application's tools by water as soon as possible.

2. Topcoat

All types of Emulsion paint (SEIV Magnolite, SEIV Magnosilk and SEIV Magnoclean, etc.).

VIII. STORAGE & PACKING

Storage: The product must be stored in accordance with nation regulations. Preferred

storage condition is cool / room temperature & dry space provided with adequate

ventilation. The containers should be sealed tightly.

Packing: 20 liters



PT SEIV Indonesia

Paint Industry - Tangerang



3

TECHNICAL DATA SHEET

SEIV MAGNOPRIME INTERIOR

IX. HEALTH & SAFETY

Please read the precaution notices displayed on the can. Spray under well-ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

X. **DISCLAIMER**

The information in this data sheet is given on the best on laboratory testing and practical experience. However as the product is often used under condition beyond our control, we can not guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.