



TECHNICAL DATA SHEET

SEIV MAGNOSILK

Product code : 431.xxx.xx

I. PRODUCT DESCRIPTION

SEIV Magnosilk is high quality interior emulsion paint which is especially formulated to give a smooth or silky and glossy appearance. It provides excellent hiding power, easy clean, fast dry, fungi and algae resistance, environmental friendly: odorless, free mercury and lead

II. RECOMMENDED USE

As topcoat for interior application. Suitable for new substrate or repainting.

III. SUBSTRATE

Applied on wall, gypsum, concrete, asbestos and ceiling

IV. TECHNICAL INFORMATION

Color	: White and according to color card
Finish	: Semi-gloss
Density	: 1.32 – 1.37 g/ml
pH	: 8.5 – 9.0
Solid content	: 55 - 60% by weight
Thickness per coat	: DFT 25 - 35 μ m
Theoretical coverage	: 12 – 17 m ² / L/ coat
Drying time, Touch dry	: ca. 30 minutes at 30 °C
Hard dry	: ca. 2 hours at 30 °C
Coating Interval	: Min. 2 hours

V. APPLICATION DATA

Remarks	: Handle with care. Stir well before used
Application method	: by brush, roller, spray air-less
Thinner	: Water
Dilution	: diluted by water 5 – 10%



TECHNICAL DATA SHEET

SEIV MAGNOSILK

VI. FEATURES & BENEFITS

1. Silky and glossy appearance
2. No splatter
3. Environmental friendly
4. Fast dry
5. Good hiding power
6. Anti-fungi
7. Free mercury and lead
8. Wash-able

VII. SURFACE PREPARATION & APPLICATION

A. SURFACE PREPARATION

The substrate must be sound, clean, dry and free from dust, dirt, waxes, oil etc. All existing coatings must be thoroughly removed by *SHRED Paint Remover* to ensure adequate adhesion.

B. APPLICATION

Recommended paint system :

1. **Primer**

SEIV Magnoprime - Alkali Resistant Primer: 1 coat (highly recommended for new substrate or repainting).

2. **Topcoat**

SEIV Magnosilk : 2 -3 coats or apply the paint as a need. Total number of coats depended on hiding power of colored paint. After coating, if there is paint in the can, close the can tightly and clean the tools thoroughly

VIII. STORAGE & PACKING

Storage : The product must be stored in accordance with nation regulations. Preferred storage condition is cool / room temperature & dry space provided with adequate ventilation. The containers should be sealed tightly.

Packing : 2.5 liters, 20 liters



TECHNICAL DATA SHEET

SEIV MAGNOSILK

IX. HEALTH & SAFETY

Please read the precaution notices displayed on the can. Spray under well-ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

X. DISCLAIMER

The information in this data sheet is given on the best on laboratory testing and practical experience. However as the product is often used under condition beyond our control, we can not guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.