



TECHNICAL DATA SHEET

SEIV MASTER GLOSS

Product code : 477.xxx.xx

I. PRODUCT DESCRIPTION

SEIV Master Gloss is synthetic topcoat made from alkyd solvent based which has good adhesion, high gloss and fast dry.

II. RECOMMENDED USE

For interior and exterior application, suitable for new substrate or repainting.

III. SUBSTRATE

Applied on metal and wood

IV. TECHNICAL INFORMATION

Color	: According color cards and special order
Finish	: Smooth & glossy
Density	: 1.00 ± 0.15 g/ml
Solid content	: approximately 65% by weight
Gloss level (GU 60°)	: 85 - 95
Thickness per coat (by brush)	: DFT 25 – 30 µm
Theoretical coverage	: 10 – 12 m ² / Liter/ coat
Drying time, Touch dry	: 1 - 2 hours at 30 °C
Hard dry	: 4 - 6 hours at 30 °C
Coating Interval	: 6 hours

V. APPLICATION DATA

Remarks	: Handle with care. Stir well before used
Application method	: by brush, roller and spray-gun
Thinner	: Thinner B
Dilution	: 5 - 10% for application with brush 15 – 30% for application with spray-gun



TECHNICAL DATA SHEET

SEIV MASTER GLOSS

VI. FEATURES & BENEFITS

1. High gloss quality
2. Fast dry
3. Provide good hiding power

VII. SURFACE PREPARATION & APPLICATION

A. SURFACE PREPARATION

The substrate must be sound, clean, dry and free from dust, dirt, waxes, oil etc. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed.

B. APPLICATION

Recommended paint system:

1. Primer

SEIV Master Gloss Primer or SEIV Chemolux Synthetic Primer: 1 coat

2. Topcoat

SEIV Master Gloss : 2 – 3 coats. Total number of coat is depended on hiding power of colored paint.

VIII. STORAGE & PACKING

Storage : The product must be stored in accordance with nation regulations. Preferred storage condition is cool / room temperature & dry space provided with adequate ventilation. The containers should be sealed tightly.

Packing : 0.8 L, 4 L, and 20 L

IX. HEALTH & SAFETY

Please read the precaution notices displayed on the can. Spray under well-ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.



TECHNICAL DATA SHEET

SEIV MASTER GLOSS

X. DISCLAIMER

The information in this data sheet is given on the best on laboratory testing and practical experience. However as the product is often used under condition beyond our control, we can not guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.