



## TECHNICAL DATA SHEET

### SEIV PRODELUX

**Product code : 439.xxx.xx**

#### **I. PRODUCT DESCRIPTION**

*SEIV Prodelux* is high quality emulsion paint designed for application in various substrate, likes : wood, metal, aluminium, concrete, plastic, glass, natural stone, wood composite and cement composite.

#### **II. RECOMMENDED USE**

For exterior and interior application, suitable for new substrate or repainting.

#### **III. SUBSTRATE**

Applied on wood, metal, asbestos, wall, concrete and ceiling.

#### **IV. TECHINCAL INFORMATION**

Color	: White and according to colors card
Finish	: Gloss
Density	: 1.00 ± 0.1 g/ml
pH	: 8.5 – 9.0
Solid content	: 50 – 55% by weight
Thickness per coat	: DFT 25 – 35 µm
Theoretical coverage per coat	: 14 – 20 m <sup>2</sup> / L/ coat
Drying time, Touch dry	: ± 30 minutes at 30 °C
Hard dry	: 60 – 90 minutes at 30 °C
Coating Interval	: Min. 1 hour

#### **V. APLICATION DATA**

Remarks	: Handle with care. Stir well before used
Application method	: by brush, roller
Thinner	: <b>Water</b>
Dilution	: Diluted by water



## TECHNICAL DATA SHEET

### SEIV PRODELUX

Application by brush or roll = 5 – 10%

Application by spray = 20%

#### VI. FEATURES & BENEFITS

1. Easy to apply
2. Non toxic
3. Non heavy metal. Free from Mercury and Lead
4. Good weather resistance
5. High gloss
6. Non flash rust and good corrosion resistance
7. Minimal *Brush Mark*

#### VII. SURFACE PREPARATION & APPLICATION

##### A. SURFACE PREPARATION

The substrate must be sound, clean, dry and free from dust, dirt, waxes, oil etc. All existing coatings must be thoroughly removed by **SHRED Paint Remover** to ensure adequate adhesion. Any resulting dust/loose particles must be removed.

##### B. APPLICATION

1. Stir thoroughly the paint before used
2. Dilute SEIV PRODELUX with water as thinner, then mix well
3. Apply to the substrate by roll, brush or spray. Let it dry. Minimal of interval coating is an hour.
4. Apply the second layer, let it dry. Total number of coats is depend of color and hiding power of the wet paint

#### VIII. STORAGE & PACKING

**Storage** : The product must be stored in accordance with nation regulations. Preferred storage condition is cool / room temperature & dry space provided with adequate ventilation. The containers should be sealed tightly.

**Packing** : 0.9 kg



## TECHNICAL DATA SHEET

### SEIV PRODELUX

#### **IX. HEALTH & SAFETY**

Please read the precaution notices displayed on the can. Apply under well-ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

#### **X. DISCLAIMER**

The information in this data sheet is given on the best on laboratory testing and practical experience. However as the product is often used under condition beyond our control, we can not guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice