



TECHNICAL DATA SHEET

SEIV SHRED PAINT REMOVER (SOLVENT BASED)

Product code : 488.100.00

I. PRODUCT DESCRIPTION

SEIV Shred Paint Remover (Solvent based) is very effective chemical liquid for removing coating from substrate. Paint remover also can be called Paint Stripper. SEIV SHRED - Paint Remover can remove all types of paint such as Ducco, Synthetic, Poly urethane, Epoxy and water based coating.

II. RECOMMENDED USE

For removing all types of paints. Paint Remover can be used for removing Ducco, Synthetic, Poly urethane, Epoxy, and Water based coating.

III. SUBSTRATE

Applied on substrate which the coating will be removed.

IV. TECHNICAL INFORMATION

Color	: Clear colorless viscous liquid
pH	: 8 - 10
Density	: 1.20 – 1.25 g/ml
Theoretical coverage per coat	: 5 - 6 m ² / kg (depend on substrate)
Stripping or softening time	: ± 10 - 120 seconds (depend on types of removed paint)

V. APPLICATION DATA

Remarks	: Handle with care. Open carefully. Stir well before used
Application method	: by brush
Thinner	: NA
Dilution	: NA

VI. FEATURES & BENEFITS

1. Fast to remove any types of paint



TECHNICAL DATA SHEET

SEIV SHRED PAINT REMOVER (SOLVENT BASED)

2. Remove all types of paint
3. Easy to apply
4. Easy to scrap

VII. PREPARATION & APPLICATION

A. PREPARATION

1. Use the gloves, google and face mask
2. Release gas from the container by punching a hole on top of container. Wait until the gas go out, then open the cap after that.
3. Stir the paint remover slowly before use until homogen .

B. APPLICATION

1. Clean the surface from dust, dirt, waxes and oil
2. Apply the paint remover on paint surface by brush
3. Wait for a minute until the surface peel off or softening in 120 second
4. Use the scrapper, kape or wire brush to peel the paint
5. If the paint has not peel-off, repeat again the step
6. After done, wash the substrate with the water to clean the paint remover

VIII. STORAGE & PACKING

Storage : The product must be stored in accordance with nation regulations. Preferred storage condition is cool / room temperature & dry space provided with adequate ventilation. The containers should be sealed tightly.

Packing : 1 kg

IX. HEALTH & SAFETY

Please read the precaution notices displayed on the can. Spray under well-ventilated conditions. Do not breath or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.



TECHNICAL DATA SHEET

SEIV SHRED PAINT REMOVER (SOLVENT BASED)

X. DISCLAIMER

The information in this data sheet is given on the best on laboratory testing and practical experience. However as the product is often used under condition beyond our control, we can not guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.