



TECHNICAL DATA SHEET

SEIV STAIN BLOCKER

Product code : 425.200.00

I. PRODUCT DESCRIPTION

SEIV Stain Blocker is a high performance, oil-based sealer which is formulated to prevent bleeding or eliminates stains. It blocks effectively on fire and smoke stains, wood tannin, crayon, lipstick, ballpoint pen, marker and food stains. It's suitable for application in any surface where fast-drying and high hiding undercoat is needed.

II. RECOMMENDED USE

All purpose of this sealer can be used under any water or solvent-based architectural paint and is suitable for new construction and remodeling. Used for interior and exterior substrate. Must be top-coated with paint. Not to be used on floors.

III. SUBSTRATE

Applied on wall, door, trim, paneling, siding, window frames and shutters

IV. TECHNICAL INFORMATION

Color	: White (can be tinted to light pastel colors)
Finish	: Doff/ Matt
Thickness per coat	: DFT 15 - 20 μ m
Theoretical coverage	: 9 - 10 m ² / Liter
Drying time, Touch dry	: ca. 30 minutes at 30 °C
Coating Interval	: about an hour
Ready to apply topcoat	: 30 days

V. APPLICATION DATA

Remarks	: Handle with care. Stir well before used
Application method	: by brush, roller, spray-less
Thinner	: NA
Dilution	: NA



TECHNICAL DATA SHEET

SEIV STAIN BLOCKER

VI. FEATURES & BENEFITS

1. Fast dry
2. Good stain blocker
3. High hiding
4. Good compatibility with all paints
5. Free mercury and lead
6. Provides alkali resistant
7. Ready to use

VII. SURFACE PREPARATION & APPLICATION

A. SURFACE PREPARATION

The surface of substrate must be sound, clean, dry and free from dust, dirt, waxes, oil etc. All existing coatings must be thoroughly removed by **SHRED Paint Remover** to ensure adequate adhesion. Always wash surface with household cleaner, appropriate cleaning solution or solvent.

Note :

Previously painted surface : Spot prime repairs or any bare areas or total surface where necessary.

New concrete, masonry or plaster : must age at least 30 days and be thoroughly dry before painting

Bare wood : sand smooth

B. APPLICATION

1. Mix paint thoroughly to ensure any settled pigment is re-dispersed
2. Apply the second layer after 1 hours and apply a topcoat within 30 days. One coat of **SEIV stain blocker** will effectively block stains including water, nicotine, ink, graffiti, crayon, marker, rust and smoke stains, so they wont bleed into the topcoat. Some stain may require a second coat



TECHNICAL DATA SHEET

SEIV STAIN BLOCKER

VIII. STORAGE & PACKING

Storage : The product must be stored in accordance with nation regulations. Preferred storage condition is cool / room temperature & dry space provided with adequate ventilation. The containers should be sealed tightly.

Packing : 4 L, 20 L

IX. HEALTH & SAFETY

Please read the precaution notices displayed on the can. Spray under well-ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

X. DISCLAIMER

The information in this data sheet is given on the best on laboratory testing and practical experience. However as the product is often used under condition beyond our control, we can not guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.