



TECHNICAL DATA SHEET

SEIV WALL FILLER

Product code : 426.100.20

I. PRODUCT DESCRIPTION

SEIV Wall Filler is economical high quality wall filler for filling pores of the wall where are cracks and imperfection surface need repair treatment so the wall surface become flat and smooth before painting.

II. RECOMMENDED USE

As wall filler to cover wall pores, then flatten and smooth the uneven part of the wall.

III. SUBSTRATE

Applied on wall which has been smooth plaster, concrete and asbestos

IV. TECHNICAL INFORMATION

Color	: White
Finish	: Doff/ Matt
Density	: 1.72 – 1.77 g/ml
Solid content	: 70 - 75% by weight
Thickness per coat	: DFT 200 µm
Theoretical coverage	: 3 – 4 m ² / Kg
Drying time, Touch dry	: ca. 30 minutes at 30 °C
Hard dry	: ca. 3 hours at 30 °C
Coating Interval	: Min. 3 hours

V. APPLICATION DATA

Remarks	: Handle with care. Stir well before used
Application method	: by brush, roller
Thinner	: Water
Dilution	: NA



TECHNICAL DATA SHEET

SEIV WALL FILLER

VI. FEATURES & BENEFITS

1. Covering wall porous
2. Flatten and smooth wall surface
3. Fungi and algae resistance
4. Alkali resistance
5. Environmental friendly : free mercury and lead

VII. SURFACE PREPARATION & APPLICATION

A. SURFACE PREPARATION

- a. The substrate must be sound, clean, dry and free from dust, dirt, waxes, oil etc. All existing coatings must be thoroughly removed by **SHRED Paint Remover** to ensure adequate adhesion.
- b. Clean up fungi and algae with 10% *tawas*/calcium hipo-chlorate solution then rinse with water and let it dried.
- c. If there are hole in the wall repair it with mixture of cement and sand
- d. The wall surface must be perfectly dry (water content 17 – 19%) and alkali content pH < 9 or let the new wall dry about 28 days in the normal condition.

B. APPLICATION

1. Apply 1-2 layers **SEIV Wall Filler** without thinning or as needed with kape/ knife.
2. Let it dry, sand the surface with sand paper number 150 – 360 until flat and smooth
3. Removed any particle from sanding process
4. The wall is ready to be painted : apply **SEIV Magnoprime** as primer first.

VIII. STORAGE & PACKING

Storage : The product must be stored in accordance with nation regulations. Preferred storage condition is cool / room temperature & dry space provided with adequate ventilation. The containers should be sealed tightly.

Packing : 2.5 kg, 5 kg, and 25 kg



TECHNICAL DATA SHEET

SEIV WALL FILLER

IX. HEALTH & SAFETY

Please read the precaution notices displayed on the can. Spray under well-ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

X. DISCLAIMER

The information in this data sheet is given on the best on laboratory testing and practical experience. However as the product is often used under condition beyond our control, we can not guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.